

CITY OF BRIDGMAN

WATER AND SEWER CONNECTIONS

INSTRUCTIONS TO DEVELOPERS AND CONTRACTORS

WARNING! BEFORE ANY WORK BEGINS ON EITHER WATER OR SEWER CONNECTIONS, TAP FEES MUST BE PAID AT CITY HALL. FAILURE TO PAY TAP FEES PRIOR TO CONNECTION COULD RESULT IN THE ISSUANCE OF A CIVIL INFRACTION CITATION.

WATER SERVICE:

1. Service line material: While the City recommends type K-copper, 200 psi black Polly is acceptable.
2. Minimum depth is 4 1/2 feet.
3. There should be minimum separation of 10 feet between the water line and the sewer line.
4. Call for an inspection before excavation is backfilled.
Water Plant – (269)465-5407 or **City Hall** – (269)465-5144
5. The water meter is to be installed by the contractor at the time of service line installation.
6. Lawn meters are available for lawn sprinkling.

SEWER SERVICE:

1. Service line material: Schedule 40 PVC
2. RESIDENTIAL: Minimum 4" line with 6" clean-out at point of connection', 4" clean-outs every 50 feet thereafter.

COMMERCIAL: Minimum 6" clean out with 6" clean out at point of connection; 6" clean-out every 50 feet thereafter.
3. 1/4" per foot of fall.
4. There should be minimum separation of 10 feet between the water line and the sewer line.
5. Call for an inspection before the excavation is backfilled.

Water Plant – (269)465-5407 or **City Hall** – (269)465-5144